

## 414PF SERIES FIXED-slats Pergola

Robust and ultra-modern, the fixed-slats pergola is an economical alternative when redesigning your outdoor space - it fits perfectly into any style of architecture: modern, contemporary or classic. Terraces, balconies, patios, swimming pools, pool houses, canopies or covered playgrounds, this new pergola system is designed for individual, collective or professional use.

### CONFIGURATIONS

Examples of self-supporting installation






(4 posts)



(9 posts)



Examples of lean-to units (2 posts)



Examples of suspended unit (no posts)



### CHARACTERISTICS

- **Elegant, low-key** design
- Numerous **configurations**
- **Thermal confort** : many inclinations possible depending on the type of slat
- Customized
- **High-durability** product
- Excellent **finish** : concealed fastenings
- **Simplified** assembly
- Available in **ready-to-install** kit form
- Available in **6 new colour models** from the Wallis&Outdoor® **design by Dank Architects** collection
- Available in all Profils Systèmes' exclusive colours : **Terra Cigala®**, **Profils Color®**, **Terre de Matières®**
- Colour shades guaranteed **up to 25 years**



### DIMENSIONS

Large sizes :

- Up to 4200 x 4300 mm per module without reinforcement
- Up to 4200 x 6000 mm per module with reinforcement
- Max. height of 3000 mm.

Customized : depth, length, height

### POSTS

- 105x105 mm self-supporting aluminium posts
- Set into the floor or on stainless steel plates

### INSTALLATION

- Simplified assembly and installation
- No noisy installation work
- Easy dismonthing for seasonal use

### RÉSISTANCE

- Max. snow load: 35 to 80 kg/sq.m.

## 414PF SERIES Slats

Various models of slats are offered to enable you to customise and modify the design and elegance of your sun shelter.




Slat type : 017-480 414-390


### THERMAL COMFORT & USE

- Fixed extruded aluminium slats, 6060 alloy, 100% recyclable
- Space between slats of 120 to 160mm (variable to choice)
- Concealed fastenings
- Slat adjustment to suit your requirements according to the type of slats
- A slat adjustment of up to 90° to modulate sun protection and ventilation


### SLAT OPTIONS




017.005




017.016




414.390




217.024




217.924




017.011




017.012




017.480 017.80  
2 possible adjustments



217.925



217.008



217.910

### RECOMMENDED SPACE BETWEEN SLATS

### Slat

### Slat adjustment for information

600 mm	217.008	90°
	217.910	90°
120 mm	017.016	35°
	017.480	45 to 90°
	217.024	55°
	217.924	50°
180 mm	017.005	26°
	017.011	26°
	017.012	26°
	217.925	26°
	414.390	57°