

Manual pergola


For more limited budgets Profils Systèmes offers a manual version of its WALLIS&Outdoor® aluminium bioclimatic pergola. Available in many different configurations, the WALLIS&Outdoor® bioclimatic pergola permits controls of both the light and ventilation of outdoor areas with its slats that can be oriented up to 140°. Fitted with a rainwater recuperation system and downpipe in any corner of your choice, the manually operated WALLIS& Outdoor® pergola offers optimal comfort to enjoy outdoor living spaces in all seasons!

CONFIGURATIONS

Example of lean-to units (2 posts) L4000 x W 6750 mm L4000 x W 6750 mm

Example of self-supporting installation

L8000 x W13500 mm



Example de suspended unit (no posts)

I 4000 x W 20250 mm



Example of offset posts

L4000 x W6750 mm



CHARACTERISTICS



- Discreet and elegant design
- Numerous configurations
- Numerous options
- Thermal comfort: orientable slats to avoid overheating in the summer and optimise solar gain in the winter
- Excellent finish: invisible fastenings
- Available as a ready-to-install kit
- Available in all Profils Systèmes' exclusive colours: Terra Cigala®, Maohé®, Eclats Métalliques®, Profils Color®, Terre de Matières®
- Colour shades guaranteed up to 25 years*



DIMENSIONS

Available up to 6750mm deep or 4000mm wide and 3000 mm high.

POSTS

- 135x135mm self-standing or invisible
- 135x135mm single piece
- 105x105 mm (lean-to only)
- Angled posts

SLATS

- Inclinaison up to 140°
- Tubular slats
- 6060, 100% recyclable aluminium alloy
- Max. surface area of slats: 27m²

WEATHER TIGHTNESS

- Rainwater recuperation system
- Peripheral gutter with downpipe in the corner of your choice (170mm/h)
- The seal between each slat ensures that the panel is watertight
- Pitch to be created in the direction of the slats, 2nd perpendicular pitch if only one downpipe
- Maximum weight of snow: 90 kg/m²





Options

A host of options are available to increase the confort of the manual pergola WALLIS& Outdoor®

LEDS LIGHTING



Three LED lighting systems with dimmer are available: The central control unit allows two sorts of lighting to be controlled, one with a dimmer.


LED RAIL



LED STRIP



LED SPOTLIGHT



FERMETURES



Sections and profiles are specifically adapted to integrate blinds and shutters. The blinds can be operated from a distance via the remote handset and the central climate control system. The blind housing features the same sleek design as the patio cover:

- Glazed or opaque doors, fixed or sliding
- ZipSCREEN solar protection









CHAUFFAGE



An infrared heating system with no visible red light is available. Its elegant, discreet design makes this infrared heating the ideal heating solution for café exteriors, winter gardens, smoking areas. With its sophisticated technique and its wireless, battery-less remote control option, this system ushers in a new generation of infrared heating.



BRUMISATEUR



The high pressure mist is generated by pumps delivering 70 bar pressure in near-silence. The water is sprayed through fine nozzles to form a delicate veil of mist. The mist spray has other uses too:

- diffusing various atmospheric products (perfume, disinfectant, insecticide)
- maintaining a virtually constant temperature and humidity

Compressor

Nozzles











